


SPECIFICATION

1. Connector A: ST/PC SM P/N: 11-AS-1-1
2. Connector B: ST/PC SM P/N: 11-AS-1-1
3. Cable Type: Duplex ϕ 3.0mm 9.0/125um SM
4. Length: 3M
5. Jacket Color: Yellow
6. Insertion Loss: <0.3 dB
7. Return Loss: >40 dB
8. Package: Individual Bag

OPERATION

Fiber Extension: $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
 Ferrule End-face Radius: $10 < R < 25\text{mm}$
 Apex Offset: < 50um
 Increase in insertion loss after 500 mating: 0.2 dB Max.
 Operation Temperature: -20° to $+70^{\circ}$
 Storage Temperature: -40° to $+80^{\circ}$
 Humidity (non-condensing) 95%RH

| | | | | | |
|---|--------------|--------------------------------------|-------------|----------|----------------------------------|
|  | DSGN | MAER | 18.MAY.2004 | ITEM NO: | AL-9STST-03I |
| | CHK | | | | |
| UNIT | M / M | APPR | | | Duplex ϕ 3.0mm 9.0/125um SM |
| SCALE | 1 / 2 | ASSMANN Electronic Components | | | |
| DWG NO: | AL-9STST-03I | | | | |