


Signature	Revision History	Date	Rev.
N.Xu	For Bulk Production	Dec:08,2007	01



NOTE:

- CABLE:UL20276 [28AWG(7/0.127)*1P+DRAIN WIRE+AL/MY+MYLAR]*7C+28AWG(7/0.127)*1P+28AWG(7/0.127)*3C +AL/MYLAR+DRAIN WIRE(7/0.127)+BRAID SHIELDS(85%)T.C PVC JACKET; OD: 8.6±0.15mm COLOR:BLACK.
- CONNECTOR:
P1&P2:DVI_D 25P: 24P+KEY MALE, GOLD FLASH CONTACT, NICKEL PLATED SHELL.
TO CONNECTOR SHELL & CABLE SHIELDING
- SHIELD:P1&P2 COPPER FOIL 360° SOLDERED
- HOOD:FIRST MOLD:MOLDED TYPE,PVC 30P,COLOR:LIGHT GREY(PANTONE 430C)
SECOND MOLD:MOLDED TYPE,PVC 45P COLOR:BLACK.
- PACKING:SEE P-0039 PACKING DRAWING
(BINDING SIZE MUST BE SMALLER THAN BLISTER)

A
B
C
D
E
F
G
H

1
2
3
4
5
6
7

Part No.		Title	
DK-110031		DVI 24+1 MALE TO DVI 24+1 MALE CABLE 2 COLOR MOLD WITH DIGITUS LOGO	
Drawn by	Date	Name	
Dec:08,2007	Dec:08,2007	N. Xu	
Checked by	Date	Name	
Dec:08,2007	Dec:08,2007	A.Dan	
Approved by	Date	Name	
Dec:08,2007	Dec:08,2007	T.Aulemann	
Scale		N/A	Sheet
Unit		MM	1/2

RoHS Compliant

S181407

ASSMANN
Electronic GmbH

A
B
C
D
E
F
G
H

Signature	Revision History	Date	Rev.
N.Xu	For Bulk Production	Dec:08,2007	01

WIRE CONNECTION

P1	WIRE COLOR	P2
1		1
2		2
3		3
3		3
4		4
5		5
6		6
7		7
9		9
10		10
11		11
11		11
12		12
13		13
14		14
15		15
16		16
17		17
18		18
19		19
19		19
20		20
21		21
22		22
23		23
24		24

SHELLBRAID SHELL SHELL

A	1	2	3	4	5	6	7
B	1	2	3	4	5	6	7
C	1	2	3	4	5	6	7
D	1	2	3	4	5	6	7
E	1	2	3	4	5	6	7
F	1	2	3	4	5	6	7
G	1	2	3	4	5	6	7
H	1	2	3	4	5	6	7

RoHS Compliant

Drawn by	Dec:08,2007	Name	N. Xu
Checked by	Dec:08,2007		ALDan
Approved by	Dec:08,2007		T.Aulemann

Part No.	DK-110031
Title	DVI 24+1 MALE TO DVI 24+1 MALE CABLE 2 COLOR MOLD WITH DIGITUS LOGO

ASSMANN
Electronic GmbH

Scale	N/A	Sheet	2/2
Unit	MM		

STR1407