

DC-11801

3 Port - DVI - USB-PS/2 Combo KVMs



Features

1. Console your Keyboard/Mouse via either way of PS/2 and/or USB arbitrarily.
2. Controls 3 DVI computers from a single console (Keyboard/Mouse) over USB and/or PS/2 connections.
3. Speaker enabled.
4. Microphone enabled.
5. Supports Windows, Linux, Mac OS9/OSX, Sun Microsystems.
6. Emulates a keyboard on each PC to allow your computers to boot normally, without a keyboard error.
7. Supports hot-swap. All devices connected to the KVM can be added or removed at any time, without shutting the unit down.
8. Supports 2 types of switching: (1) Hardware Push Button, (2) Hot-Keys on PS/2 and/or USB of keyboard arbitrarily.
9. Supports Auto-Scan function to switch video automatically among computers in preset intervals sequentially.
10. Supports LED display for PC status monitoring.
11. Supports DVI UXGA resolutions up to 1600 x 1200 @ 60HZ.
12. Supports Beeper during switching enabled.
13. Self powered through USB connection.
14. Fully compliant with the USB 1.1/ 2.0 specification
15. Comply with DVII specification and support analog display devices

System Requirements

Console

- DVI monitor capable of the highest resolution
- PS/2 and/or USB Keyboard/Mouse

Computer or Server

The following equipment must be equipped with each computer or server.

- DVI connector
- Type A USB port

Specification

Number Of Computers Controlled	3	
Selection Method	Push Button and Hot-Key (PS/2 and/or USB Keyboard)	
LEDs	Red for PC Selection Green for PC On-Line ready	
PC Connectors	Video	3 x DVI UXGA female
	USB	3 x USB - B type female
	Speaker	3 x audio female jacket
	Microphone	3 x audio female jacket
Console Ports	Keyboard	1 x 6 pin mini-DIN female
	Mouse	1 x 6 pin mini-DIN female
	Video	1 x DVI UXGA female
	Keyboard	1 x USB - A type female
	Mouse	1 x USB - A type female
	Speaker	1 x audio female jacket
	Microphone	1 x audio female jacket
Auto-Scan Interval	From 5 to 250 Seconds	
DDC, DDC2 DVI UXGA monitor	Up to resolution: 1600 x 1200	
Hot Swappable	Yes	
Operating systems supported	Windows 98SE/ME/2000/XP/2003 Server, Linux Mac OS9/OSX and Sun Microsystems	
Device driver	No Need	
Power	By PS/2 and/or USB or External Power Adaptor (Optional)	
Cable Length	6 feet (1.80 Meter)	
Dimensions (L X W X H)	21.5 x 8.8 x 4.5 cm (5.5 X 3 X 1.7 inches)	
Unit Weight	650 g	
Housing material	Metal	
Operating Temperature	32~ 122°F (0~ 50°C)	
Humidity	0%~80%RH	

Art.Nr. **DC-11801** EAN-Nr. **4016032201090** DVI - USB-PS/2 Combo-KVM Switch 1User, 4PCs, with Audio