

Signature	Revision History	Date	Rev.
		Dec:20,2005	01

1	2	3	4	5	6	7	A									
<p>NOTES:</p> <p>1. CABEL:UL-2919 COAX*5C 28AWG(7/0.127)TINNED COPPER (75 OHMS) INSULATION:FO-PE INNER JACKET:PVC COLOR:RED, GREEN,BLUE,WHITE,BLACK. OD:Ø2.5± 0.1mm UL-1354+ AL/MYLAR+BRAID SHIELD(65%)+OUTER JACKET:PVC OD:9.0± 0.2mm COLOR:BLACK.</p> <p>2. CONNECTOR: P1:HDI5P MALE GOLD FLASH CONTACT,NICKEL PLATED SHELL (9TH PIN UNLOAD) P2~P6 :BNC MALE GOLD FLASH CONTACT NICKEL PLATED SHELL</p> <p>3. SHIELD: P1:COPPER-FOIL 360° SOLDER CONNECTOR SHELL & CABLE BRAID</p> <p>4. HOOD:ALL MOLDED TYPE, PVC 45P, COLOR:BLACK.</p> <p>5. THUMB SCREW:#4-40UNC*2</p> <p>6. ELECTRICAL TEST:100% OPEN SHORT MIS WIRE TEST CONTACT RESISTANCE 3 Ω MAX</p> <p>INSULATION RESISTANCE 20M Ω MIN</p> <p>7. PACKING:SEE P-0039 REV.C PACKING DRAWING + EAN CODE PACKING TYPE: DB VP4 (HANKING SIZE MUST BE SMALLER THAN PACKING)</p>																
<p>1</p> <p>2</p> <p>3</p> <p>4</p> <p>5</p> <p>6</p> <p>7</p>																
<p>EAN CODE: 4016032064213</p>																
<table border="1"> <tr> <td>Drawn by</td> <td>Dec:20,2005</td> <td>Norman Xu</td> </tr> <tr> <td>Checked by</td> <td>Dec:20,2005</td> <td>Alex Dan</td> </tr> <tr> <td>Approved by</td> <td></td> <td></td> </tr> </table>				Drawn by	Dec:20,2005	Norman Xu	Checked by	Dec:20,2005	Alex Dan	Approved by			<p>Part No. AK 553/F</p>			
Drawn by	Dec:20,2005	Norman Xu														
Checked by	Dec:20,2005	Alex Dan														
Approved by																
<p>ASSMANN Electronic GrmbH</p>				<p>Title HDB 15M to 5 BNC/M cable 2.0M</p>												
Scale		N/A		Sheet		2/2										
Unit		MM														

S781407