

Signature	Revision History	Date	Rev.
	For Bulk Production	Dec:08,2007	01

1	2	3	4	5	6	7	A
							B
<p>NOTES:</p> <p>1.CABLE:UL2725 [26AWG(1/0,404)*2F INS:HD-PE ID:1.3*2.7+DRAIN WIRE 28AWG(1/0,32)*2C+AL/MY]*2C INNER JACKET:PVC OD:7.3*2.1mm +AL/MY+BRAID(16/10/0.1)PVC JACKET, COLOR: BLACK, OD:9.0*4.0mm, IMPEDANCE: 100 OHM.</p> <p>2.CONNECTOR: P1&amp;P2:SATA II 7P RIVETING TYPE CRIMP TYPE PBT BLACK G/F W/METAL SHELL 3.SHIELD:COPPER-FOIL 4.HOOD:FIRST MOLD:MOLDED TYPE,PVC 30P,COLOR:LIGHT GREY(PANTONE 430C) SECOND MOLD:MOLDED TYPE,PVC 45P COLOR:BLACK. 5.TEST REQUEST: 100% OPEN SHORT MIS WIRE TEST CONTACT RESISTANCE 3 ohm MAX. INSULATION RESISTANCE 10M ohm MIN. HI-POT DC300V/0.01SEC. 6.PACKING: SEE P-0039 PACKING DRAWING. (BINDING SIZE MUST BE SMALLER THAN BLISTER)</p>							C
<p><b>PIN ASSIGNMENT</b></p>							D
<p><b>Part No.</b> <b>DK-126002</b></p>							E
<p><b>Title</b> SATA Cable, Connect,Ssata L-Type, 2 COLOR MOLD WITH DIGITUS LOGO</p>							F
<p><b>Scale</b> N/A</p>							G
<p><b>Unit</b> MM</p>							H
<p><b>Sheet</b> 1/1</p>							H

RoHS Compliant

**ASSMANN**  
Electronic GmbH

Drawn by	Dec:08,2007	N. Xu
Checked by	Dec:08,2007	ALDan
Approved by	Dec:08,2007	T.Aulemann

S181407