

8 / 16 Port - USB-PS/2 Combo KVMs



Features

1. Console your Keyboard/Mouse via either way of PS/2 and/or USB arbitrarily.
2. Complex connections with PCs via either way of PS/2 and/or USB arbitrarily.
3. Controls 8 or 16 computers from a single console (Keyboard/Mouse) over PS/2 and/or USB connections.
4. Supports Windows, Linux, Mac OS9/OSX, Sun Microsystems.
5. On-Screen-Display (OSD) & Cascade Chain functions.
 - OSD is intuitive menu driven for quick and efficient navigation.
 - 3 level cascades: up to 3 levels; control up to 64/256/4096 PCs, from a single console; cascaded units don't need special configuration.
6. Emulates PS/2 or USB keyboard on each PC to allow your computers to boot normally without a keyboard error.
7. Supports hot-pluggable. All devices connected to the KVM can be added or removed at any time, without shutting the unit down.
8. Supports 3 types of switching:
 - (1) Hardware Push Button
 - (2) Hot-Keys on PS/2 and/or USB of keyboard
 - (3) Menu driven OSD (On Screen Display).
9. Supports Auto-Scan function to switch video automatically among computers in preset intervals sequentially by OSD menu driven.
10. Supports LED display for PC and/or server status monitoring.
11. Supports VGA resolutions up to 2048 x 1536 @ 85HZ.
12. Supports Beeper during Switching enabled.
13. Powered with external power adaptor connection.
14. Fully compliant with the USB 1.1/ 2.0 specification.
15. Rack Mountable in 19" system tack (1U).

System Requirements

Console

- A VGA, SVGA, Multisync monitor capable of the highest resolution.
- PS/2 and/or USB Keyboard/Mouse

Computer or Server

The following equipment must be equipped with each computer or server:

- A VGA, SVGA or Multisync card.
- Type A USB port and/or PS/2 6 pin mini-DIN for Keyboard and Mouse.

Specification

Number Of Computers Controlled		8 or 16
Selection Method		Push Button, Hot-Key (PS/2 and/or USB Keyboard) or On-Screen-Display (OSD) & Cascade Chain
LEDs		Red for PC Selection Green for PC On-Line ready
PC Connectors	Video	1 x HDB-15 male
		(PS/2 & USB signal combined)
Console Ports	Keyboard	1 x 6 pin mini-DIN female
	Mouse	1 x 6 pin mini-DIN female
	Video	1 x HDB-15 female
	Keyboard	1 x USB – A type female
	Mouse	1 x USB – A type female
Auto-Scan Interval		Adjustable time setting by OSD menu driven
DDC, DDC2 monitor		Yes (Max. Resolution: 2048x1536)@85Hz
Hot Swappable		Yes
Operating systems supported		Windows 98SE/ME/2000/XP/2003 Server, Linux Mac OS9/OSX and Sun Micro Systems
Device driver		No Need
Power		By external power adaptor
Dimensions (L X W X H)		44 x 15.7 x 4.5 cm (17.3 x 6.1 x 1.5 inch)
Unit Weight		~1750 g / ~1900 g
Housing material		Metal
Operating Temperature		32~ 122°F (0~ 50°C)
Humidity		0%~80%RH

Art.Nr. **DC-13201** EAN-Nr. **4016032201021** USB-PS/2 Combo-KVM Switch 1User, 8PCs
 Art.Nr. **DC-14201** EAN-Nr. **4016032201038** USB-PS/2 Combo-KVM Switch 1User, 16PCs