



## SPECIFICATION

1. Connector A: MT-RJ MM P/N: 11-MM-1-1
2. Connector B: MT-RJ MM P/N: 11-MM-1-1
3. Cable Type: Duplex  $\varnothing 3.0\text{mm}$  62.5/125um MM
4. Length: 2M
5. Jacket Color: Orange
6. Insertion Loss:  $< 0.5$  dB
7. Package: Individual Bag

## OPERATION

Fiber Extention:  $-0.05\mu\text{m} < H < +0.05\mu\text{m}$   
 Ferrule End-face Radius:  $10 < R < 25\text{mm}$   
 Apex Offset:  $< 50\mu\text{m}$   
 Increase in insertion loss after 500 mating: 0.2 dB Max.  
 Operation Temperature:  $-20^{\circ}$  to  $+70^{\circ}$   
 Storage Temperature:  $-40^{\circ}$  to  $+80^{\circ}$   
 Humidity (non-condensing) 95%RH

	DSGN	MAER	18.MAY.2004	ITEM NO:	AL-6MTRJMTRJ-02I
	CHK				
UNIT	M / M	APPR			Duplex $\varnothing 3.0\text{mm}$ 62.5/125um MM
SCALE					
DWG NO:	ASSMANN Electronic Components				
AL-6MTRJMTRJ-02I					