



SPECIFICATION

- | | |
|-------------------|----------------------------------|
| 1. Connector A | ST/PC MM P/N: 11-AM-2-1 |
| 2. Cable Type | Simplex ϕ 0.9mm 50/125um MM |
| 3. Length | 2M |
| 4. Jacket Color | Orange |
| 5. Insertion Loss | <0.5 dB |
| 6. Package | Individual Bag |

OPERATION :

- Fiber Extention : $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
- Ferrule End-face Radius : $10 < R < 25\text{mm}$
- Apex Offset : $< 50\mu\text{m}$
- Increase in insertion loss after 500 mating : 0.2 dB Max.
- Operation Temperature : $-20\phi\text{X}$ to $+70\phi\text{X}$
- Storage Temperature : $-40\phi\text{X}$ to $+80\phi\text{X}$
- Humidity (non-condensing) 95%RH

"#": Matching DIM.	DSGN	MAER	18.MAY.2004	ITEM NO:	AL-5FPST-02I															
"#": Important DIM.	CHK																			
Others General DIM.	APPR				Simplex ϕ 0.9mm 50/125um MM															
<table border="0"> <tr> <td>UNIT</td> <td>TOLERANCE</td> <td></td> </tr> <tr> <td>GENERAL DIMENSIONS</td> <td>MM</td> <td></td> </tr> <tr> <td>Sϕ.XXXE</td> <td>± 0.005</td> <td></td> </tr> <tr> <td>X.XX</td> <td>± 0.05</td> <td></td> </tr> <tr> <td>X.X</td> <td>± 0.1</td> <td></td> </tr> </table>						UNIT	TOLERANCE		GENERAL DIMENSIONS	MM		S ϕ .XXXE	± 0.005		X.XX	± 0.05		X.X	± 0.1	
UNIT	TOLERANCE																			
GENERAL DIMENSIONS	MM																			
S ϕ .XXXE	± 0.005																			
X.XX	± 0.05																			
X.X	± 0.1																			
<table border="0"> <tr> <td>DWG NO:</td> <td colspan="5">ASSMANN Electronic Components</td> </tr> <tr> <td>AL-5FPST-02I</td> <td colspan="5"></td> </tr> </table>						DWG NO:	ASSMANN Electronic Components					AL-5FPST-02I								
DWG NO:	ASSMANN Electronic Components																			
AL-5FPST-02I																				